


Anziehvorschrift für Zylinderkopf		020.030 passend für / suitable for adaptable à / adaptable a Mitsubishi	 Das Original
Tightening Instructions for Cylinder Head			
Instructions de serrage pour culasse			
Prescripciones de apriete para culatas			

Schraubenkopf / Head shape
 Tête de vis / Cabeza de tornillo
 

709.270
M 10 x 95

Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete

7	5	2	4	10
9	3	1	6	8

Anziehen/ Tightening/ Serrage/ Apriete	* ☐ ➤ ➤	75 Nm 20 Nm 90° 90°
---	---	------------------------------

Zeichenerklärung / Explanations / Explication / Explicacion

* ★ ☐ ● ➤	neue Zylinderkopf- schrauben verwenden Warmlauf (80°C) Schrauben einzeln lösen und wieder anziehen Setzzeit Drehwinkel	use new cylinder head bolts warm up time (80°C) loosen and tighten each bolt relaxation time torque angle	utiliser des vis neuves chauffage (80°C) desserrer et serrer vis par vis durée de tassement angle de serrage	emplar tornillos nuevos calentamiento (80°C) aflojar y apretar tornillo a tornillo tiempo de espera ángulo de giro
--	--	---	--	---

Motortyp / Engine type / Type de moteur / Tipo de motor

± 0,45 mm, Ø 82 mm

Mot.: 4G92, 4G93 1,6 ltr.-1,8 ltr.
66-103 kW (90-140 PS)

Carisma, Colt, Lancer

ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601	*020.030*
--	------------------