

Anziehvorschrift für Zylinderkopf		071.292 passend für / suitable for adaptable à / adaptable a Renault/Dacia/Nissan	 Das Original
Tightening Instructions for Cylinder Head			
Instructions de serrage pour culasse			
Prescripciones de apriete para culatas			
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete	
			
151.890 M 10x1,5x117			
Anziehen/ Tightening/ Serrage/ Apriete	* 20 Nm ➤ 240°±6°		
Zeichenerklärung / Explanations / Explication / Explicacion			
* ★ ☐ ● ➤	neue Zylinderkopf- schrauben verwenden Warmlauf (80°C) Schrauben einzeln lösen und wieder anziehen Setzzeit Drehwinkel	use new cylinder head bolts warm up time (80°C) loosen and tighten each bolt relaxation time torque angle	utiliser des vis neuves chauffage (80°C) deserrer et serrer vis par vis durée de tassement angle de serrage emplar tornillos nuevos calentamiento (80°C) aflojar y apretar tornillo a tornillo tiempo de espera ángulo de giro
Motortyp / Engine type / Type de moteur / Tipo de motor			
Ø 80,5 mm			
Mot.: K4J, K4M 1,4 ltr. - 1,6 ltr. 16V			
Clio, Kangoo, Laguna, Megane, Modus, Scenic, Twingo, Dacia Duster, Logan			
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601		*071.292*	