


Anziehvorschrift für Zylinderkopf		124.420 passend für / suitable for adaptable à / adaptable a Mitsubishi	 Das Original
Tightening Instructions for Cylinder Head			
Instructions de serrage pour culasse			
Prescripciones de apriete para culatas			

Schraubenkopf / Head shape
 Tête de vis / Cabeza de tornillo
 

003.930
M11x1,25x97

Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete

8	6	1	3	9
10	4	2	5	7

Anziehen/	✱	78 Nm
Tightening/	☐	20 Nm
Serrage/	➤	90°
Apriete	➤	90°

Zeichenerklärung / Explanations / Explication / Explicacion

✱	neue Zylinderkopf-schrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos
★	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)
☐	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera
➤	Drehwinkel	torque angle	angle de serrage	ángulo de giro

Motortyp / Engine type / Type de moteur / Tipo de motor
 ✱ 0,4 mm
 Mot.: 4G64
 2,4 Itr. 106-110 kW (144-150 PS)
 Galant, Grandis, Lancer, Outlander,
 Space Runner, Space Wagon

ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601	*124.420*
--	------------------