


Anziehvorschrift für Zylinderkopf			149.332		 Das Original																				
Tightening Instructions for Cylinder Head			passend für / suitable for																						
Instructions de serrage pour culasse			adaptable à / adaptable a																						
Prescripciones de apriete para culatas			Audi																						
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo			Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete																						
			<table><tr><td>10</td><td>6</td><td>1</td><td>3</td><td>7</td></tr><tr><td>8</td><td>4</td><td>2</td><td>5</td><td>9</td></tr><tr><td>8</td><td>4</td><td>2</td><td>5</td><td>9</td></tr><tr><td>10</td><td>6</td><td>1</td><td>3</td><td>7</td></tr></table>			10	6	1	3	7	8	4	2	5	9	8	4	2	5	9	10	6	1	3	7
10	6	1				3	7																		
8	4	2				5	9																		
8	4	2				5	9																		
10	6	1	3	7																					
130.120 M 12x1,5x159																									
Anziehen/ * 35 Nm Tightening/ 60 Nm Serrage/ ➤ 90° Apriete ➤ 90°																									
Zeichenerklärung / Explanations / Explication / Explicacion																									
✱	neue Zylinderkopf-schrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos																					
★	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)																					
□	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo																					
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera																					
➤	Drehwinkel	torque angle	angle de serrage	ángulo de giro																					
Motortyp / Engine type / Type de moteur / Tipo de motor																									
✱ 1,1 mm, Ø 83,8, 1 Loch/hole/trou/agujero Cyl. 5-8																									
Mot.: BVN, BMC, BTR, CEMA 4,2 Ltr. TDI																									
Audi A8, Q7																									
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601			*149.332*																						