

Anziehvorschrift für Zylinderkopf		239.870	 Das Original	
Tightening Instructions for Cylinder Head		passend für / suitable for adaptable à / adaptable a		
Instructions de serrage pour culasse		PSA		
Prescripciones de apriete para culatas				
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete		
A  B 		⑧ ④ ① ⑤ ⑨ ⑦ ③ ② ⑥ ⑩		
Anziehen/ Tightening/ Serrage/ Apriete ✱ 50 Nm ★ 78 Nm ● 12 min ● 120 min □ 78 Nm				
Zeichenerklärung / Explanations / Explication / Explicacion				
✱	neue Zylinderkopf-schrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos
★	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)
□	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera
➤	Drehwinkel	torque angle	angle de serrage	ángulo de giro
Motortyp / Engine type / Type de moteur / Tipo de motor				
74 mm Ø, -/1,30 mm ÷				
Peugeot 104 Mot.XV3 bis >Mot.6335439				
Mot.XV5/XV8 ab Mot.6335440>				
205 Mot.XV8 02/1983>11/1985				
Talbot Samba Mot.XV5/XV8 ab 10/1981>				
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601			*239.870*	