


Anziehvorschrift für Zylinderkopf		244.421	 Das Original															
Tightening Instructions for Cylinder Head		passend für / suitable for																
Instructions de serrage pour culasse		adaptable à / adaptable a																
Prescripciones de apriete para culatas		GM / GMC																
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete																
	<table><tr><td>10</td><td>6</td><td>2</td><td>4</td><td>8</td></tr><tr><td></td><td></td><td>RH</td><td></td><td></td></tr><tr><td>9</td><td>5</td><td>1</td><td>3</td><td>7</td></tr></table>			10	6	2	4	8			RH			9	5	1	3	7
	10	6	2	4	8													
			RH															
	9	5	1	3	7													
<table><tr><td>9</td><td>5</td><td>1</td><td>3</td><td>7</td></tr><tr><td></td><td></td><td>LH</td><td></td><td></td></tr><tr><td>10</td><td>6</td><td>2</td><td>4</td><td>8</td></tr></table>			9	5	1	3	7			LH			10	6	2	4	8	
9	5	1	3	7														
		LH																
10	6	2	4	8														
Anziehen/ Tightening/ Serrage/ Apriete	* ➤ ➤ ➤ ➤ ➤	Pos. 1-10: 80 Nm Pos. 1-10: 90° Pos. 1-8: 60° Pos. 9 LH: 40° Pos. 9 RH: 60° Pos. 10: 60°																
Zeichenerklärung / Explanations / Explication / Explicacion																		
✱	neue Zylinderkopf-schrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos														
★	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)														
☐	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo														
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera														
➤	Drehwinkel	torque angle	angle de serrage	ángulo de giro														
Motortyp / Engine type / Type de moteur / Tipo de motor																		
Ø: 104 mm; 1/2: 1,33 mm																		
Mot: L86 6,2 ltr V8 313 KW (426 PS)																		
Suburan, Yukon XL, Escalade ESV																		
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601			*244.421*															