



Anziehvorschrift für Zylinderkopf		598.620 passend für / suitable for adaptable à / adaptable a Renault, Dacia	 Das Original	
Tightening Instructions for Cylinder Head				
Instructions de serrage pour culasse				
Prescripciones de apriete para culatas				
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete		
 649.390 M10x1,5x123				
Anziehen/ Tightening/ Serrage/ Apriete	* ➤	Pos 1-10: 20 Nm Pos 1-10: 25 Nm Pos 1-10: 270° ±20°		
Zeichenerklärung / Explanations / Explication / Explicacion				
* ★ □ ● ➤	neue Zylinderkopf- schrauben verwenden Warmlauf (80°C) Schrauben einzeln lösen und wieder anziehen Setzzeit Drehwinkel	use new cylinder head bolts warm up time (80°C) loosen and tighten each bolt relaxation time torque angle	utiliser des vis neuves chauffage (80°C) deserrer et serrer vis par vis durée de tassement angle de serrage	emplar tornillos nuevos calentamiento (80°C) aflojar y apretar tornillo a tornillo tiempo de espera ángulo de giro
Motortyp / Engine type / Type de moteur / Tipo de motor				
Mot: H5F				
1.2 ltr 84-97 kW (115-132 PS)				
Renault Megane III, Scénic III,				
Dacia Dokker, Lodgy, Duster				
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601			*598.620*	