

Anziehvorschrift für Zylinderkopf		724.780		 Das Original															
Tightening Instructions for Cylinder Head		passend für / suitable for adaptable à / adaptable a																	
Instructions de serrage pour culasse		Fiat																	
Prescripciones de apriete para culatas																			
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete																	
		<table><tr><td>8</td><td>6</td><td>2</td><td>5</td><td>10</td></tr><tr><td>7</td><td>3</td><td>1</td><td>4</td><td>9</td></tr><tr><td>14</td><td>12</td><td>11</td><td>13</td><td>15</td></tr></table>			8	6	2	5	10	7	3	1	4	9	14	12	11	13	15
8	6	2	5	10															
7	3	1	4	9															
14	12	11	13	15															
760.510 M 12x1,25x134																			
Anziehen/ Tightening/ Serrage/ Apriete		M 12: * 50 Nm 100 Nm ➤ 90° ➤ 90°																	
		M 8: * 30 Nm																	
Zeichenerklärung / Explanations / Explication / Explicacion																			
*	neue Zylinderkopf- schrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos															
★	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)															
□	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo															
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera															
➤	Drehwinkel	torque angle	angle de serrage	ángulo de giro															
Motortyp / Engine type / Type de moteur / Tipo de motor																			
Ø: 83 mm; ✱: 1,85 mm																			
Mot: 1,7-1,9 ltr Diesel/Turbodiesel 42-68 kW (57-92 PS)																			
145, 146, 155, Dedra, Delta, Prisma Ducato, Duna, Fiorino, Palio, Punto, Regata, Ritmo II, Strada, Talento, Temptra, Tipo, Uno																			
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601			*724.780*																