


Anziehvorschrift für Zylinderkopf		736.220 passend für / suitable for adaptable à / adaptable a BMW	 Das Original																				
Tightening Instructions for Cylinder Head																							
Instructions de serrage pour culasse																							
Prescripciones de apriete para culatas																							
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete																					
		<table><tr><td>⑧</td><td>⑥</td><td>②</td><td>④</td><td>⑩</td></tr><tr><td>⑨</td><td>③</td><td>①</td><td>⑤</td><td>⑦</td></tr></table> <table><tr><td>⑨</td><td>③</td><td>①</td><td>⑤</td><td>⑦</td></tr><tr><td>⑧</td><td>⑥</td><td>②</td><td>④</td><td>⑩</td></tr></table>		⑧	⑥	②	④	⑩	⑨	③	①	⑤	⑦	⑨	③	①	⑤	⑦	⑧	⑥	②	④	⑩
⑧	⑥	②	④	⑩																			
⑨	③	①	⑤	⑦																			
⑨	③	①	⑤	⑦																			
⑧	⑥	②	④	⑩																			
714.750 M 10x1,5x160																							
Anziehen/ Tightening/ Serrage/ Apriete	* ➤ ➤	30 Nm 90° 90°																					
Zeichenerklärung / Explanations / Explication / Explicacion																							
✳	neue Zylinderkopf-schrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos																			
★	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)																			
□	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo																			
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera																			
➤	Drehwinkel	torque angle	angle de serrage	ángulo de giro																			
Motortyp / Engine type / Type de moteur / Tipo de motor																							
Mot. N62 B48																							
E60/E61 550i																							
E63/E64 650i																							
E65/E66 750i, Li																							
E53/E70 X5 4.8i, is																							
±0,75mm																							
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601			*736.220*																				