

Anziehvorschrift für Zylinderkopf		752.177 passend für / suitable for adaptable à / adaptable a Saab	 Das Original
Tightening Instructions for Cylinder Head			
Instructions de serrage pour culasse			
Prescripciones de apriete para culatas			
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete	
⑧④①⑤⑨ ⑦③②⑥⑩			
Anziehen/ Tightening/ Serrage/ Apriete	* ☐ ➤	30 Nm 60 Nm 80 Nm 90 ° 80 Nm 90°	
Zeichenerklärung / Explanations / Explication / Explicacion			
* ★ ☐ ● ➤	neue Zylinderkopf- schrauben verwenden Warmlauf (80°C) Schrauben einzeln lösen und wieder anziehen Setzzeit Drehwinkel	use new cylinder head bolts warm up time (80°C) loosen and tighten each bolt relaxation time torque angle	utiliser des vis neuves chauffage (80°C) deserrer et serrer vis par vis durée de tassement angle de serrage emplar tornillos nuevos calentamiento (80°C) aflojar y apretar tornillo a tornillo tiempo de espera ángulo de giro
Motortyp / Engine type / Type de moteur / Tipo de motor			
99 L, GL, LA 99 LE, LEA, EMS 99 Turbo 900 GL, GLE, GLS, EMS 900 Turbo 4 Cyl. 1985 ccm			
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601		*752.177*	