

# MERCEDES BENZ INSERTS FOR SUSPENSION SPRINGS

TECHNICAL INFORMATION NO. 1094

## VEHICLE MANUFACTURER / MODELS:

|                      |                             |
|----------------------|-----------------------------|
| <b>Mercedes Benz</b> | SL (R107, R129)             |
|                      | W (114 115 116 126 201 202) |
|                      | W/C/S123, W/C/S124          |

## MERCEDES BENZ INSERTS FOR SUSPENSION SPRINGS

| No. | Position | Spacing | No. of studs | RUVILLE-No. | MB OE-No.:               |
|-----|----------|---------|--------------|-------------|--------------------------|
| 1.  | front    | 13 mm   | 2            | 875102      | 1233211484               |
| 2.  | front    | 18 mm   | 3            | 875103      | 1233211584               |
| 3.  | front    | 23 mm   | 4            | 875104      | 1233211684               |
| 4.  | front    | 8 mm    | 1            | 875108      | 2013210984               |
| 5.  | front    | 13 mm   | 2            | 875109      | 2013211084               |
| 6.  | front    | 18 mm   | 3            | 875110      | 2013211184               |
| 7.  | front    | 23 mm   | 4            | 875111      | 2013211284               |
| 8.  | rear     | 9,5 mm  | 1            | 875117      | 1153251644<br>1153252344 |
| 9.  | rear     | 14 mm   | 2            | 875118      | 1153252344<br>1153252344 |
| 10. | rear     | 19 mm   | 3            | 875119      | 1153252444               |
| 11. | rear     | 8 mm    | 1            | 875120      | 2013250944               |
| 12. | rear     | 13 mm   | 2            | 875121      | 2013251044               |
| 13. | rear     | 18 mm   | 3            | 875122      | 2013251144               |

### INSTALLATION INSTRUCTIONS:

Always check the struts/bushings of the wheel suspension and steering when replacing the suspension spring.

### IMPORTANT NOTE!

Note the specifications of the vehicle manufacturer!

When changing the suspension springs in the models named on the left, RUVILLE recommends that the suspension spring inserts are changed at the same time. The spacing height is clearly indicated by the number of studs.

Comply with the instructions of the OE manufacturer for the front and rear vehicle height of the respective model and the fitted special features.



Image 1: inserts for suspension springs



### INFORMATION

Corresponding spare parts can be found in our online catalogue at [www.ruville.de](http://www.ruville.de). Where reference is made to the spare parts numbers of the vehicle manufacturers, this is only for the purposes of comparison.