



FLEXCORD PLUS COOLANT

PRODUCT TYPE: COOLING SYSTEMS

RECOMMENDED FOR: Light-duty automotive coolant applications. Designed to withstand severe conditions under the bonnet. This very flexible hose is also recommended for light-duty industrial applications. The hose absorbs vibrations and shocks and has a strong, supple body.

RESISTANT TO: Resistant to the harmful conditions under the bonnet; heat, ozone and coolant additives.



CONSTRUCTION:

- SHAPE:** Straight
- TUBE:** EPDM
- REINFORCEMENT:** Aramid
- WIRE:** -
- COVER:** EPDM

STANDARDS:

- SAE NORM** -
- DIN NORM** -

TEMPERATURE:



	PN								
		mm	"	mm	m	mm	bar	bar	#
CH8X1	4272-10080	8	5/16	12	1	135	4	16	3
CH10X1	4272-10100	10	3/8	14	1	135	4	16	3
CH12X1	4272-10120	12	1/2	16	1	135	4	16	3
CH15X1	4272-10150	15	5/8	19	1	120	4	16	3
CH18X1	4272-10180	18	11/16	22	1	120	4	16	3
CH20X1	4272-10200	20	13/16	24	1	120	3	12	3
CH22X1	4272-10220	22	7/8	26	1	90	3	12	3
CH25X1	4272-10250	25	1	29	1	90	3	12	3
CH28X1	4272-10280	28	1 1/8	32	1	90	3	12	3
CH30X1	4272-10300	30	1 3/16	34	1	90	3	12	3
CH32X1	4272-10320	32	1 1/4	36	1	90	3	12	3
CH35X1	4272-10350	35	1 3/8	39	1	90	3	12	3
CH38X1	4272-10380	38	1 1/2	43	1	60	3	12	3
CH40X1	4272-10400	40	1 9/16	45	1	60	2	8.5	3
CH42X1	4272-10420	42	1 5/8	47	1	60	2	8.5	3
CH45X1	4272-10450	45	1 3/4	50	1	45	2	8.5	3
CH48X1	4272-10480	48	1 7/8	53	1	45	2	8.5	3
CH50X1	4272-10500	50	2	55	1	45	2	8.5	3