

Arbeitsscheinwerfer

LED



WxD: 114 x 32 mm
ECE norm: R10
Light Distribution: Short distance lighting
Info: with accessories
 Electromagnetic Compatibility (EMC)

Rated Voltage: 12 V
 24 V
Height 1 / 2: 114 / 146 mm
Housing material: Plastic

Mounting	LEDs	Lumen lm	Colour Temperature K	IP-Code	DU	Article no.
mounting Deutsch Connector	13	1200	6000	IP 68 	1	80690331
Accessories			Cable lenght mm	see	DU	
Base, worklight			200	Katalog06	1	80691310
Plug Housing Set TE Connectivity Deutsch DT				Katalog04	1	50390595
				Katalog04	1	50390600
Base, worklight Magnet Base				Katalog06	1	80691000

LED



WxD: 122 x 26 mm
ECE norm: R10
Light Distribution: Short distance lighting
Info: with accessories
 Electromagnetic Compatibility (EMC)

Rated Voltage: 12 V
 24 V
Height 1 / 2: 122 / 150 mm
Housing material: Plastic

Mounting	LEDs	Lumen lm	Colour Temperature K	IP-Code	DU	Article no.
mounting Deutsch Connector	14	1200	6000	IP 68 	1	80690332
Accessories			Cable lenght mm	see	DU	
Base, worklight			200	Katalog06	1	80691310
Plug Housing Set TE Connectivity Deutsch DT				Katalog04	1	50390595
				Katalog04	1	50390600
Base, worklight Magnet Base				Katalog06	1	80691000