



1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO Silicone Spray

VAICO No.:

V60-1101

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

Highly effective silicone spray for lubrication, treatment and maintaining of metal, plastic and rubber components.

- Optimum lubrication
- Protects against moisture
- Temperature resistant (from -50 °C to +250 °C.)
- Odorless
- Colorless
- Fat-free

3. USE INSTRUCTIONS

Suitable for lubricating for all moving parts in the passenger car or commercial vehicle sector, in the plastics-, printing- or paper industry. Also usable as surface care or protection in the plastics industry.

4. APPLICATION INSTRUCTIONS

Spray evenly on the cleaned surface from a distance of approx. 20 cm /8".



PRODUCT DATA



5. SPECIFICATIONS

With solvent

TYPICAL VALUES	TEST METHOD	UNIT	VAICO V60-1101
Colour	visually	-	colourless
Odour	-	-	neutral
Density, 20 °C	DIN 51757	g/cm ³	0,745
Pour point	DIN ISO 3016	°C	< -30
Viscosity, 40 °C	DIN 51550	mm ² /s	2,5

After solvent evaporation

TYPICAL VALUES	TEST METHOD	UNIT	VAICO V60-1101
Density, 20 °C	DIN 51757	g/cm ³	0,965
Viscosity, 40 °C	DIN 51550	mm ² /s	350
Flash point	-	°C	> 250
Temperature range	-	°C	-30 to +150