



1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VA-HALDEX

VAICO No.:

V60-0363, V60-0364

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

Special hydraulic oil for Haldex-Clutch at vehicles with All-Wheel-Drive.

- Reliable protection against wear even in cases with the highest requirements
- Matched friction characteristics, protects against foaming
- Optimum lubrication even at low temperatures
- Excellent corrosion and rust protection
- Excellent cooling ability
- High viscosity index

3. USE INSTRUCTIONS

VA-HALDEX oil is particularly suitable for All-Wheel, Quattro and 4Motion drives.

It should be replaced every 30,000 - 60,000 km to prevent damage to the drive train.

4. PERFORMANCE DATA

Spezifikationen:

- VW G 060 175 A2 (850 ML)
- GM 93 165 387
- Land Rover LR 054941
- Opel 19 40 057
- Volvo 1 161 641, 30 759 648, 31 325 136, 31 367 940, 31 367 941



PRODUCT DATA SHEET



TYPICAL VALUES	METHOD	UNIT	VAICO VA-HALDEX
Density at 15°C	DIN EN ISO 12185	kg/cm3	859
Viscosity at 40°C	DIN 51 562	mm2/s	24,5
Viscosity at 100°C	DIN 51 562	mm2/s	5,5
Viscosity index (VI)	DIN ISO 2909	-	169
Pour point	ASTM D 7346	°C	-54
Colour	-	-	yellow