

WOLF MINERAL FLUID LHM

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Date of issue: 14/08/2003

Revision date: 20/02/2015

Supersedes: 20/10/2014

Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name. : WOLF MINERAL FLUID LHM
Product code : 5077
Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use
Industrial/Professional use spec. : Non-dispersive use
Used in closed systems
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

WOLF OIL CORPORATION N.V.
Georges Gilliotstraat, 52
2620 Hemiksem - België
T 0032 (0)3 870 00 00 / 0476/23 33 14
info@wolfoil.com

1.4. Emergency telephone number

Emergency number : 0032 (70) 245 245

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Asp. Tox. 1 H304
Aquatic Chronic 3 H412
Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

R52/53
Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

Signal word (CLP) : Danger.
Hazardous ingredients : Baseoil - unspecified, White Mineral Oil (petroleum)
Hazard statements (CLP) : H304 - May be fatal if swallowed and enters airways
H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P331 - Do NOT induce vomiting
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations

WOLF MINERAL FLUID LHM

Safety Data Sheet

according to Regulation (EC) No. 453/2010

EUH phrases : EUH208 - Contains Phenol, isopropylated, phosphate (3:1)(68937-41-7). May produce an allergic reaction

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
Baseoil - unspecified	(CAS No) 72623-86-0 (EC no) 276-737-9 (EC index no) 649-482-00-X	50 - 100	Not classified
White Mineral Oil (petroleum)	(CAS No) 8042-47-5 (EC no) 232-455-8	25 - 50	Not classified
2,6-di-tert-butyl-p-cresol	(EC no) 204-881-4 (REACH-no) 01-2119565113-46	0,1 - 1	N; R50/53
Phenol, isopropylated, phosphate (3:1)	(CAS No) 68937-41-7 (EC no) 273-066-3	0,1 - 1	Repr.Cat.3; R62 Repr.Cat.3; R63 Xn; R48/22 N; R51/53

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Baseoil - unspecified	(CAS No) 72623-86-0 (EC no) 276-737-9 (EC index no) 649-482-00-X	50 - 100	Asp. Tox. 1, H304
White Mineral Oil (petroleum)	(CAS No) 8042-47-5 (EC no) 232-455-8	25 - 50	Asp. Tox. 1, H304
2,6-di-tert-butyl-p-cresol	(EC no) 204-881-4 (REACH-no) 01-2119565113-46	0,1 - 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Phenol, isopropylated, phosphate (3:1)	(CAS No) 68937-41-7 (EC no) 273-066-3	0,1 - 1	Skin Sens. 1, H317 Repr. 2, H361 STOT RE 2, H373 Aquatic Chronic 2, H411

Full text of R-, H- and EUH-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Call a POISON CENTER/doctor/physician if you feel unwell. Assure fresh air breathing.
First-aid measures after skin contact : Wash skin with mild soap and water.
First-aid measures after eye contact : In case of eye contact, immediately rinse with clean water for 10-15 minutes.
First-aid measures after ingestion : Do not induce vomiting. Rinse mouth. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/injuries after skin contact : Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/injuries after eye contact : Not expected to present a significant eye contact hazard under anticipated conditions of normal use.
Symptoms/injuries after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

Ingestion of this product may lead to chemical pneumonia and even death.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water fog. Foam. Powder. Dry chemical product.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Precautionary measures fire : Exercise caution when fighting any chemical fire.

WOLF MINERAL FLUID LHM

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Impound and recover large spill by mixing it with inert granular solids.
Methods for cleaning up	: Detergent. Take up liquid spill into absorbent material sand, saw dust, kieselguhr.
Other information	: Spill area may be slippery. Use suitable disposal containers.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.
Handling temperature	: < 40 °C
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage temperature	: < 40 °C
Storage area	: Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

: 5 mg/m³ for oil mists (TWA, 8h-workday) recommended, based upon the ACGIH TLV (Analysis according to US NIOSH Method 5026, NIOSH Manual of Analytical Methods, 3rd Edition).

8.2. Exposure controls

Personal protective equipment	: Safety glasses. Gloves.
-------------------------------	---------------------------



Hand protection	: Wear suitable gloves resistant to chemical penetration.
Skin and body protection	: No special clothing/skin protection equipment is recommended under normal conditions of use.
Respiratory protection	: No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Oily liquid.
Colour	: green.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available

WOLF MINERAL FLUID LHM

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Freezing point	: -55 °C
Boiling point	: > 200
Flash point	: > 125 °C @ ASTM D92
Self ignition temperature	: > °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 840 kg/m³ @ 15°C
Solubility	: Slightly soluble, the product remains on the water surface.
Log Pow	: No data available
Viscosity, kinematic	: 18 mm²/s @ 40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

Strong oxidizers. acids. Bases.

10.6. Hazardous decomposition products

None under normal conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

WOLF MINERAL FLUID LHM	
LD50 oral rat	> mg/kg
LD50 dermal rabbit	> mg/kg
White Mineral Oil (petroleum) (8042-47-5)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
2,6-di-tert-butyl-p-cresol	
LD50 oral rat	> 2930 mg/kg OECD 401
LD50 dermal rat	> 2000 mg/kg OECD 402

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified

WOLF MINERAL FLUID LHM

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Aspiration hazard : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

White Mineral Oil (petroleum) (8042-47-5)

LC50 fishes 1	> 100 mg/l
---------------	------------

12.2. Persistence and degradability

WOLF MINERAL FLUID LHM

Persistence and degradability	Not soluble in water, so only minimally biodegradable.
-------------------------------	--

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Additional information : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with ADR / RID / ADN / IMDG / ICAO / IATA

14.1. UN number

No dangerous good in sense of transport regulations

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

No additional information available

14.6.2. Transport by sea

No additional information available

14.6.3. Air transport

No additional information available

14.6.4. Inland waterway transport

No additional information available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions

Contains no REACH candidate substance

WOLF MINERAL FLUID LHM

Safety Data Sheet

according to Regulation (EC) No. 453/2010

15.1.2. National regulations

Germany

Water hazard class (WGK) : 1 - slightly hazardous to water

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Other information : The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

Full text of R-, H- and EUH-phrases::

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Repr. 2	Reproductive toxicity Category 2
Skin Sens. 1	Skin sensitisation Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H304	May be fatal if swallowed and enters airways
H317	May cause an allergic skin reaction
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
R48/22	Harmful: danger of serious damage to health by prolonged exposure if swallowed
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R62	Possible risk of impaired fertility
R63	Possible risk of harm to the unborn child
N	Dangerous for the environment
Xn	Harmful

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.