

# EXTENDTECH 75W90 GL 5

22/05/2017 2209

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This is a transmission oil with an exceptionally high viscosity index. It exhibits excellent fluidity at low temperatures and ensures a long life of the oil and gears.

# **APPLICATIONS**

This is a special transmission oil with "extreme pressure" properties, specifically composed in order to prevent corrosion on copper alloys. It is applied in modern gear boxes and some rear axles, especially where gear shift problems occur when using thicker oils.

# FEATURES

Frictional properties : smooth shift performance. Anti-wear protection : long transmission life. Extended oil life : proven resistance to oil degradation.

### SPECIFICATION LEVEL

```
API
```

```
GL-5
```

MIL

MIL-L-2105 D

### TYPICAL CHARACTERISTICS

Method	Unit	Average results
ASTM D4052	g/ml	0.881
ASTM D445	mm²/s	81
ASTM D445	mm²/s	15
ASTM D2270		196
ASTM D6892	°C	-45
ASTM D2983	mPa.s	130.000
ASTM D92	°C	206
	ASTM D4052 ASTM D445 ASTM D445 ASTM D2270 ASTM D6892 ASTM D2983	ASTM D4052 g/ml ASTM D445 mm²/s ASTM D445 mm²/s ASTM D2270 ASTM D6892 °C ASTM D2983 mPa.s

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV G. Gilliotstraat 52 – 2620 Hemiksem – Belgium Tel. +32 (0)3 870 00 00 www.wolflubes.com

