

VITALTECH

5W40 GAS

22/05/2017
22116

This is a full synthetic lubricant based on carefully selected very high quality base oils and additives of the latest generation. It is specially designed to meet the strict requirements of LPG, CNG and Dual Fuel powered passenger cars. The gas engines give higher combustion temperatures and therefore need this special technology to protect the valves and neutralize the acid compounds created.

APPLICATIONS

This oil is used in gas engines for passenger cars, powered by LPG, CNG and Dual Fuel. The high quality allows extended drain intervals, according to the specific requirements of manufacturers.

FEATURES

Total gas engines protection: outstanding engine cleanliness and durability.
Cold start: excellent fluidity at low temperature.
Drain interval extension

SPECIFICATION LEVEL

| | | | |
|------|------------|---------|---------|
| ACEA | C3-08 | MB | 229.3 |
| ACEA | A3/B4-10 | RENAULT | RN 0700 |
| ACEA | A3/B4-08 | RENAULT | RN 0710 |
| API | SN/CF | VW | 502 00 |
| FIAT | 9.55535-T2 | VW | 505 00 |
| MB | 226.5 | | |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.855 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 81.1 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 13.6 |
| Viscosity index | ASTM D2270 | | 172 |
| B.N. (HClO ₄ method) | ASTM D2896 | mg KOH/g | 10.0 |
| Pour point | ASTM D6892 | °C | -42 |
| Sulfated Ash | ASTM D874 | Mass % | 0.8 |
| Flash Point COC | ASTM D92 | °C | 222 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfiubes.com

