



EXTENDTECH

75W80 GL 5

03/07/2016
2300

This is an extreme-pressure lubricant for gear boxes, specially formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

APPLICATIONS

It is recommended for all hypoid transmissions and is also suitable for spiral bevel gear, worm wheels and most transaxles.

FEATURES

Frictional properties : smooth shift performance.
Anti-wear protection : long transmission life.
Extended oil life : proven resistance to oil degradation.

SPECIFICATION LEVEL

| | | | |
|-----|--------------|-----|--------------|
| API | GL-5 | MIL | MIL-L-2105 D |
| MIL | MIL-L-2105 C | | |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|-------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.869 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 49.6 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 9.23 |
| Viscosity index | ASTM D2270 | | 171 |
| Pour point | ASTM D6892 | °C | -51 |
| Brookfield viscosity at -40°C | ASTM D2983 | mPa.s | 65000 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

