

OFFICIALTECH

75W/90 G 50

03/07/2016
2306

This is a full synthetic lubricant based on carefully selected very high quality base oils. Due to its specifically selected composition it avoids gear squawk and prolongs the lifetime of the gear lubricant. It noticeably improves low temperature gear shifts and ensures an easy gear change at high temperature.

APPLICATIONS

This product is specifically formulated for gearboxes with integrated differentials of front-wheel driven cars.

FEATURES

Frictional properties : very smooth gear shifting, no vibration.
Anti-wear protection : significantly extended transmission life.
Extended oil life : excellent thermal and oxidation stability.

SPECIFICATION LEVEL

| | | | |
|------|--------------|-----|------------|
| API | GL-4 + | MIL | MIL-L-2105 |
| BMW | MTF LT-4 | VW | 501 50 |
| FORD | WSD-M2C200-C | | |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|-------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.858 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 71 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 14 |
| Viscosity index | ASTM D2270 | | 206 |
| Pour point | ASTM D6892 | °C | -45 |
| Brookfield viscosity at -40°C | ASTM D2983 | mPa.s | 110000 |
| Flash Point COC | ASTM D92 | °C | 200 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfiubes.com

