



# GUARDTECH

## ATF D

22/05/2017  
3001

This is an oil, with a high viscosity index, especially designed to satisfy the requirements of General Motors for the use in the first generation of automatic transmissions. Very good anti-wear and detergent qualities, anti-foam and anti-corrosion.

### APPLICATIONS

This oil is used in automatic transmissions, power steering, torque convertors and hydraulic systems.

### FEATURES

Anti-wear protection : long transmission life.  
Extended oil life : optimized thermal and oxidation stability.

### SPECIFICATION LEVEL

ALLISON	C2/C3	GM	6032-M DEXRON
ATF	TYPE A SUFFIX A	MB	236.2
DIN	HLP-D		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Color	ASTM D1500		red
Density at 15°C	ASTM D4052	g/ml	0.858
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	37,1
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	7,6
Viscosity index	ASTM D2270		179
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	2,1
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	50.000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

