

GUARDTECH

ATF F/G

03/07/2016
3002

ATF TYPE F/G oil has been specifically designed for use in automatic FORD-transmissions (GLIDE). It is characterized by its very high viscosity index and low pour point, which ensure optimal performance in a broad temperature range.

APPLICATIONS

ATF TYPE F/G is specifically intended for use in automatic gear boxes of FORD-passenger cars. It can also be used in some other makes, for which an equal product as the FORD-specifications prescribed.

FEATURES

Anti-wear protection : long transmission life.
Extended oil life : optimized thermal and oxidation stability.

SPECIFICATION LEVEL

FORD	ESW-M2C33-F	JD	JDM J21A
FORD	ESP-M2C33-G	VOLVO	97330
FORD	SQM2-9007-AA		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.869
Kinematic viscosity at 40°C	ASTM D445	mm²/s	36
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.3
Viscosity index	ASTM D2270		173
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	30000
Flash Point COC	ASTM D92	°C	206
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

