



# OFFICIALTECH

## ATF MB

22/05/2017  
3011

This is a full synthetic lubricant based on carefully selected very high quality base oils, mainly intended for all MB 7-speed automatic transmissions and NAG-V Sport transmissions. It provides excellent frictional durability and superior performance.

### APPLICATIONS

This ATF is recommended for the 7G-Tronic and 5-Speed automatic transmissions of Mercedes-Benz. Due to its specific composition and characteristics, it is not suitable for other applications.

### FEATURES

Anti-wear protection : significantly extended transmission life.  
Frictional properties : very smooth gear shifting, no vibration.  
Extended oil life : excellent thermal and oxidation stability.

### SPECIFICATION LEVEL

MB 236.14

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	28.6
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	5.9
Viscosity index	ASTM D2270		154
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	11800
Flash Point COC	ASTM D92	°C	206
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfubes.com](http://www.wolfubes.com)

