



OFFICIALTECH

MULTI VEHICLE ATF HD-LD

22/05/2017
3015

This transmission fluid is an ultra high performance heavy duty synthetic transmission fluid. It is designed to deliver significantly extended drain capabilities. It contains superior quality synthetic base oils and advanced additive technologies and is suitable for use in automatic transmission systems in both heavy duty trucks and buses.

APPLICATIONS

This transmission fluid is designed for extended drain in heavy duty automatic truck and bus as well as off-road equipment transmissions.

FEATURES

Very smooth gear shifting, no vibration.
Significantly extended transmission life.
Excellent thermal and oxidation stability.

SPECIFICATION LEVEL

MAN	339 Z3	VOLVO	STD 1273,41 (97341)
MAN	339 V1	VOLVO	STD 1273,40 (97340)
MB	236.9	ZF	TE-ML 14C
VOITH	H55.6336xx	ZF	TE-ML 20C
VOITH	H55.6335xx	ZF	TE-ML 04D

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.844
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	38.7
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.3
Viscosity index	ASTM D2270		158
Pour point	ASTM D6892	°C	-54
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	15400
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

