

# OFFICIALTECH

## 5W20 MS-FE

23/10/2017  
65612

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is extremely fuel-efficient and meets the requirements of the new Ford EcoBoost petrol engines. It ensures a reduction of fuel consumption on partial and full load operation as well as reduction of exhaust emission. It has excellent cold starting behavior giving a very good operating reliability.

### APPLICATIONS

Meets the requirements of the Ford WSS-M2C948-B specification and is mandatory for Ford EcoBoost 1.0 3-cylinder engines and is required for further EcoBoost petrol engines. This oil can also be used where the vehicle manufacturer specifies a motor oil ACEA A1/B1 or API SN.

### FEATURES

Total engine protection: performance in keeping the engine clean.  
Fuel economy: superior fuel economy and CO<sub>2</sub> reduction.  
Cold start: excellent fluidity at low temperature.

### SPECIFICATION LEVEL

ACEA	C5-16	FORD	WSS-M2C948-A
ACEA	A1/B1-12	ILSAC	GF-5
API	SN	JAGUAR-LAND	STJLR.03.5004
FORD	Approval WSS-M2C948-B	ROVER	

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	42.3
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	7.9
Viscosity index	ASTM D2270		162
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	7.6
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	5500
Sulfated Ash	ASTM D874	Mass %	0.8
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfub.com](http://www.wolfub.com)

