



# MULTIPURPOSE GREASE 3

22/05/2017  
9103

This is a lubricating grease for general applications, where no specific requirements are made. This grease has a good oxidation stability, so that it can ensure long-lasting lubrication. It is water-resistant and has good temperature characteristics. Therefore it can be used at high temperatures and it stays pumpable at low temperatures making it suitable for bearing lubrication.

## APPLICATIONS

This grease can be used in both industrial and automotive applications. It is suitable for a wide range of plain and rolling bearings. Temperature range: -30°C to +120°C, Max. +130°C

## FEATURES

- . Good mechanical stability.
- . Good corrosion protection.
- . Suitable also in wet environment.

## SPECIFICATION LEVEL

DIN	51502	ISO	6743
DIN	K3K-30	ISO	L-XCCFA3

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Texture	Visual		Smooth
Colour	VISUAL		Light Brown
NLGI Classification	ASTM D217		3
Worked Penetration (60 strokes)	ISO 2137	0.1 mm	235
Dropping point	ISO 2176/IP 396	°C	190
Four Ball Weld Load	ASTM D2596/DIN51350:4	N	2000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

