

ALL-PURPOSE EP NR. 0

22/05/2017
9182

This is a semi-liquid Lithium grease. It has an excellent low temperature pumpability, maintaining its good flow property. By the use of "Extreme Pressure" additives, this grease is resistant to heavy shocks and loads. It has also excellent anti-corrosion, anti-rust and anti-oxidant-properties, which increase the life span of the grease and the lubricated parts.

APPLICATIONS

This grease can be used in both industrial and automotive applications. The consistency of the product makes it suitable for use in centralised lubrication systems that require semi-fluid grease. The product is also suitable for use in gearboxes. Temperature range: -30°C to +120°C, Max. +130°C

FEATURES

- . Easy to pump at low temperature.
- . Good mechanical stability.
- . High load carrying capacity.
- . Good corrosion protection.

SPECIFICATION LEVEL

| | | | |
|-----|---------|-----|----------|
| DIN | 51502 | ISO | 6743 |
| DIN | KP0K-30 | ISO | L-XCCFBO |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---------------------------------|-----------------------|--------|-----------------|
| Texture | Visual | | Smooth |
| Colour | VISUAL | | Yellowish-Brown |
| NLGI Classification | ASTM D217 | | 0 |
| Worked Penetration (60 strokes) | ISO 2137 | 0.1 mm | 370 |
| Dropping point | ISO 2176/IP 396 | °C | 170 |
| Four Ball Weld Load | ASTM D2596/DIN51350:4 | N | 2600 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

