



## WOLF ECOTECH 0W16 SP/RC G6 XFE

13/08/2020

16152

### Description

Thanks to its low viscosity and outstanding fluidity this oil significantly reduces wear and ensures fuel savings and lower CO2 emissions. Optimized additive package reduces soot and deposits and keeps the engine clean.

### Application

This product has been specifically developed to meet the challenging requirements of the latest ILSAC GF-6 B standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

### Specifications

|       |                                     |
|-------|-------------------------------------|
| API   | SN Plus - SN Plus/RC<br>SP<br>SP/RC |
| ILSAC | GF-6 B                              |

### Characteristics

| <u>Test</u>                     | <u>Unit</u>        | <u>Method</u> | <u>Average result</u> |
|---------------------------------|--------------------|---------------|-----------------------|
| Density at 15°C                 | g/ml               | ASTM D4052    | 0.846                 |
| Kinematic viscosity at 40°C     | mm <sup>2</sup> /s | ASTM D445     | 34.8                  |
| Kinematic viscosity at 100°C    | mm <sup>2</sup> /s | ASTM D445     | 6.9                   |
| Viscosity index                 |                    | ASTM D2270    | 163                   |
| B.N. (HClO <sub>4</sub> method) | mg KOH/g           | ASTM D2896    | 8.5                   |
| Pour point                      | °C                 | ASTM D6892    | -45                   |
| Flash Point COC                 | °C                 | ASTM D92      | 220                   |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

