



WOLF ECOTECH 10W30 SP/RC G6

13/08/2020

16156

Thanks to its low viscosity and excellent fluidity, this oil significantly reduces wear and ensures fuel savings and lower CO2 emissions. Optimized additive package reduces soot and deposits and keeps the engine clean.

Applications

This product has been specially developed to meet the challenging requirements of the latest ILSAC GF-6 A standard, where fuel consumption and CO2 reduction are important. It delivers the performance required for the latest gasoline-powered American and Asian passenger car requirements.

Performance

This state-of-the-art, low-viscosity, high-flow oil guarantees an easy cold start and significantly reduces wear, while at the same time contributing to fuel consumption.

Specification level

API	SN Plus	ILSAC	GF-5
	SN/RC		GF-6 A
	SP		
	SP/RC		

Typical characteristics

<u>Test</u>	<u>Unity</u>	<u>Method</u>	<u>Result</u>
Density at 15°C	g/ml	ASTM D4052	0.852
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	64.2
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	10.6
Viscosity index		ASTM D2270	155
B.N. (HCLO4 method)	mg KOH/g	ASTM D2896	8.5
Pour point	°C	ASTM D6892	-42
Flash point COC	°C	ASTM D92	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 (0)3 870 00 00

www.wolf lubes.com

