

BRAKE FLUID DOT 4 LV

17/02/2021
5093

This brake fluid is especially recommended for use in hydraulic brake and clutch systems of vehicles fitted with ESP (Electronic Stability Program) and ABS (Anti-lock Braking System) with a high boiling point and outstanding performance at very low temperatures.

APPLICATIONS

Its high wet boiling point (172°C) is superior to conventional fluids DOT 3 and DOT 4 and therefore enables longer product lifetime. The viscosity at - 40 °C of this DOT4 LV is lower than conventional brake fluids allowing an easier fluid circulation in micro-valves of anti-locking systems for better response of ESP, ABS and ASR.

FEATURES

Boiling point: very high boiling point, safe braking.
Anti-corrosion properties: complete brake system protection.

SPECIFICATION LEVEL

BMW	QV 34 1	SAE	J 1703
FMVSS	116 DOT 4	SAE	J 1704
FMVSS	116 DOT3	VW	501 14
GM	GMW 3356	VW	TL 766-Z
ISO	4925 Class 3,4&6		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	2.10
pH	ASTM D1287		8.53
Equilibrium Reflux Boiling Point (ERBP)	ASTM D1120	°C	267
Wet Equilibrium Reflux Boiling Point (WERBP)	ASTM D1120	°C	172
Density at 20°C	ASTM D4052	g/ml	1.049
Kinematic viscosity at -40°C	ASTM D445	mm ² /s	675

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

