

# OFFICIALTECH

## 5W30 C4

20/10/2020  
65608

This is a full synthetic lubricant based on carefully selected very high quality base oils, specifically formulated to provide superior protection of the after-treatment systems of Renault engines.

### APPLICATIONS

Gasoline and diesel engines of passenger cars with or without turbo which are equipped with a DPF and a TWC (Three-Way Catalyst).

### FEATURES

Aftertreatment protection : full aftertreatment system protection.  
Total engine protection : outstanding engine cleanliness and durability.  
Fuel economy : lower fuel consumption and CO2 emissions.

### SPECIFICATION LEVEL

ACEA	C4	MB	Approval 226.51
ACEA	C3	MB	229.31
FIAT	9.55535-S4	RENAULT	Approval RN 0720
MB	Approval 229.51		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm²/s	67.1
Kinematic viscosity at 100°C	ASTM D445	mm²/s	11.8
Viscosity index	ASTM D2270		173
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	6.4
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	5800
Sulfated Ash	ASTM D874	Mass %	0.5
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfubcs.com](http://www.wolfubcs.com)

