



WOLF OFFICIALTECH 0W30 LL III FE

DESCRIPTION :

This is a full synthetic lubricant based on carefully selected very high quality base oils. It is specifically formulated to meet the most demanding VW specifications available today - VW 504.00 and 507.00 - as well as the Long Life III requirements of the VAG Group. It is a Mid SAPS oil which meets Euro 4 and Euro 5 norms and provides protection to the Diesel Particulate Filter. This viscosity grade provides a proven fuel economy over a 5W30 grade.

APPLICATIONS :

Backwards compatible: 504.00 and 507.00 supersedes all previous VW specifications (502.00, 503.00, 503.01, 505.00, 506.00 and 506.01). All vehicles in the VAG Group (Volkswagen, Audi, Seat, Skoda) with extended oil drain intervals (30.000 km or 2 years) from 2007 onwards. Note: For V10 TDI and 5-cylinder 2.5 TDI engines, prior to 2007, where the 506.01 specification has to be used, this oil is not recommended. The first generation engines with pump injector units should use the 505.01 specification.

SPECIFICATION LEVEL :

ACEA	C2*/C3
VW	504 00/507 00/TL 52 545
PORSCHE	C30

TYPICAL CHARACTERISTICS :

Test	Unit	Method	Average result
Density at 15°C	g/ml	ASTM D4052	0.842
Kinematic viscosity at 40°C	mm²/s	ASTM D445	59.0
Kinematic viscosity at 100°C	mm²/s	ASTM D445	11,7
Viscosity index		ASTM D2270	197
B.N. (HClO4 method)	mg KOH/g	ASTM D2896	8.3
Pour point	°C	ASTM D6892	-48
Colour		VISUAL	Brown

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

65620

July, 2020.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolf lubes.com

