

WOLF OFFICIALTECH 0W20 UHPD EXTRA FE

24/06/2020

65632

This full synthetic lubricant has been developed to offer high performance and ultimate protection of the latest IVECO engines. Its particular formulation gives the product extraordinary features.

Application

This lubricant is developed for IVECO Stralis fitted with Euro 6 Cursor engines equipped with fuel economy package (FEP1). It shows extreme Fuel Economy capacities and has a Low SAPS formulation. It complies with the IVECO 18-1804 CLASSE TVL-LS specification.

Performance

Its particular resistance to oxidation allows better performance of the variable geometry turbine, under harsh operating conditions. It improves cleanliness and protection of the lubricated engine up to the maximum oil drain intervals.

Specifications

IVECO 18-1804 Classe TLV LS

Characteristics

| <u>Test</u> | <u>Unit</u> | Method | Average result |
|------------------------------|-------------|-------------------|----------------|
| Density at 15°C | g/ml | ASTM D4052 | 0.845 |
| Kinematic viscosity at 40°C | mm²/s | ASTM D445 | 48.2 |
| Kinematic viscosity at 100°C | mm²/s | ASTM D445 | 8.9 |
| Viscosity index | | ASTM D2270 | 167 |
| B.N. (HCLO4 method) | mg KOH/g | ASTM D2896 | 12.8 |
| Pour point | °C | ASTM D6892 | -66 |
| Flash Point COC | °C | ASTM D92 | 220 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

