



WOLF OFFICIALTECH 5W30 C3 RN

7/08/2020

65637

This synthetic engine oil formulation guarantees a cleaner and better performing engine without lowering the oil drain interval. The broad applicability of this lubricant enables you to offer perfect maintenance to different vehicles of several major brands.

Application

This engine oil can be used in systems with or without exhaust gas aftertreatment where C3 engine oils are required. Furthermore, this engine oil has the official Renault RN 17 approval . This means also that you can use this lubricant where RN0700 & RN0710 were previously required, enabling you to service several Dacia and Renault models with this engine oil.

Specifications

ACEA	C3
RENAULT	RN17 approval

Characteristics

<u>Test</u>	<u>Unit</u>	<u>Method</u>	<u>Average result</u>
Density at 15°C	g/ml	ASTM D4052	0.849
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	60.3
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	11.8
Viscosity index		ASTM D2270	197
B.N. (HCLO4 method)	mg KOH/g	ASTM D2896	8.0
Pour point	°C	ASTM D6892	-39
Sulfated Ash	Mass %	ASTM D874	0.78

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolf lubes.com

