



OE LEVEL TECH 5W30 LL

12/08/2020

75602

DESCRIPTION :

This is a specifically composed full synthetic lubricant formulated to meet Long Life III requirements of the VAG Group. This Mid SAPS oil complies with the EU Euro 4 and 5 standards and provides excellent protection to the Diesel Particulate Filter. This product may not be available in your region. Please, consult your local sales contact for more information.

APPLICATIONS :

Due to its special composition it is possible to apply this product for the latest VW 504.00/507.00 requirements. This oil is also suitable for use in most engines of German car manufacturers like BMW, Mercedes-Benz and Porsche.

SPECIFICATION LEVEL :

ACEA	C2* /C3	MB	229.31/229.51
API	SN	PORSCHE	C30
BMW	LOGLIFE-04	VW	503 01/504 00/507 00

TYPICAL CHARACTERISTICS :

Test	Unit	Method	Average result
Density at 15°C	g/ml	ASTM D4052	0.856
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	68
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	11,7
Viscosity index		ASTM D2270	169
Pour point	°C	ASTM D6892	-39
Flash Point COC	°C	ASTM D92	230
B.N. (HClO4 method)	mg KOH/g	ASTM D2896	8.3
Sulfated Ash	Mass %-	ASTM D874	0,7

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 (0)3 870 00 00

www.wolf lubes.com

