

PRO RACING

10W60 M

This is a full synthetic lubricant based on carefully selected very high quality base oils of the latest generation for the lubrication of all gasoline and diesel engines with turbo.

APPLICATIONS

4 stroke gasoline engines, multi-valves, turbo. 4 stroke diesel engines, with or without turbo.

FEATURES

Cold start : very good fluidity at low temperature.

Total engine protection : outstanding engine cleanliness and durability.

SPECIFICATION LEVEL

ACEA	A3/B4-08	MB	229.3 Level
API	SN/CF	VW	501 01
BMW	M-MODELS	VW	505 00
BMW	LONGLIFE-01 Level		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm²/s	156
Kinematic viscosity at 100°C	ASTM D445	mm²/s	25
Viscosity index	ASTM D2270		194
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	9.5
Pour point	ASTM D6892	°C	-36
Sulfated Ash	ASTM D874	Mass %	1.0
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION