

ACTIVE DEFENCE

ATF D

This is an oil, with a high viscosity index, especially designed to satisfy the requirements of General Motors for the use in the first generation of automatic transmissions. Very good anti-wear and detergent qualities, anti-foam and anti-corrosion.

APPLICATIONS

This oil is used in automatic transmissions, power steering, torque convertors and hydraulic systems.

FEATURES

Anti-wear protection : long transmission life.

Extended oil life : optimized thermal and oxidation stability.

SPECIFICATION LEVEL

ALLISON	C2/C3	GM	6032-M DEXRON
ATF	TYPE A SUFFIX A	MB	236.2
DIN	HLP-D		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Color	ASTM D1500		red
Density at 15°C	ASTM D4052	g/ml	0.858
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	37,1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7,6
Viscosity index	ASTM D2270		179
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	2,1
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	50.000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION®