RETRO FORMULA **20W50**

Light detergent multigrade oil, made of paraffinic base oils and selected additives. It offers a good protection against oxidation and corrosion.

APPLICATIONS

This oil can be used in less loaded diesel engines with natural aspiration and 4 stroke gasoline engines, when the API-class SD is required.

FEATURES

Total engine protection : engine protection and cleanliness.

SPECIFICATION LEVEL

API SD/CC **MIL** MIL-L-2104 B

FORD WSS-M2C101-B

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.887
Kinematic viscosity at 40°C	ASTM D445	mm²/s	155
Kinematic viscosity at 100°C	ASTM D445	mm²/s	18
Viscosity index	ASTM D2270		129
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	3.9
Pour point	ASTM D6892	°C	-24
CCS viscosity at -15°C	ASTM D5293	mPa.s	8400
Sulfated Ash	ASTM D874	Mass %	0.7
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION