

# OEM SPECIFIC

## 5W30 C4

*This is a full synthetic lubricant based on carefully selected very high quality base oils, specifically formulated to provide superior protection of the after-treatment systems of Renault engines.*

### APPLICATIONS

*Gasoline and diesel engines of passenger cars with or without turbo which are equipped with a DPF and a TWC (Three-Way Catalyst).*

### FEATURES

*Aftertreatment protection : full aftertreatment system protection.*

*Total engine protection : outstanding engine cleanliness and durability.*

*Fuel economy : lower fuel consumption and CO2 emissions.*

### SPECIFICATION LEVEL

<b>ACEA</b>	C4-12	<b>MB</b>	226.51
<b>MB</b>	229.51	<b>RENAULT</b>	Approval RN 0720

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.854
Kinematic viscosity at 40°C	ASTM D445	mm²/s	68
Kinematic viscosity at 100°C	ASTM D445	mm²/s	11,7
Viscosity index	ASTM D2270		169
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	7.2
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	6300
Sulfated Ash	ASTM D874	Mass %	0.5
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION®**