

MULTIPURPOSE GREASE 2

This is a lubricating grease for general applications, where no specific requirements are made. This grease has a good oxidation stability, so that it can ensure long-lasting lubrication. It is water-resistant and has good temperature characteristics. Therefore it can be used at high temperatures and it stays pumpable at low temperatures making it suitable for bearing lubrication.

APPLICATIONS

This grease can be used in both industrial and automotive applications. It is suitable for a wide range of plain and rolling bearings. Temperature range: -30°C to +120°C, Max. +130°C

FEATURES

- . Multiple use in industrial and automotive applications.
- . Good mechanical stability
- . Good corrosion protection
- . Suitable for bearings even in wet environment

SPECIFICATION LEVEL

DIN	51502	ISO	6743
DIN	K2K-30	ISO	L-XCCEA2

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Texture	Visual		Smooth
Colour	VISUAL		Yellowish Brown
NLGI Classification	ASTM D217		2
Worked Penetration (60 strokes)	ISO 2137	0.1 mm	265-295
Dropping point	ISO 2176/IP 396	°C	190
Four Ball Weld Load	ASTM D2596/DIN51350:4	N	2000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION