

# MULTIPURPOSE GREASE 3

*This is a lubricating grease for general applications, where no specific requirements are made. This grease has a good oxidation stability, so that it can ensure long-lasting lubrication. It is water-resistant and has good temperature characteristics. Therefore it can be used at high temperatures and it stays pumpable at low temperatures making it suitable for bearing lubrication.*

## APPLICATIONS

*This grease can be used in both industrial and automotive applications. It is suitable for a wide range of plain and rolling bearings. Temperature range: -30°C to +120°C, Max. +130°C*

## FEATURES

- . Good mechanical stability.
- . Good corrosion protection.
- . Suitable also in wet environment.

## SPECIFICATION LEVEL

<b>DIN</b>	51502	<b>ISO</b>	6743
<b>DIN</b>	K3K-30	<b>ISO</b>	L-XCCFA3

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Texture	Visual		Smooth
Colour	VISUAL		Light Brown
NLGI Classification	ASTM D217		3
Worked Penetration (60 strokes)	ISO 2137	0.1 mm	235
Dropping point	ISO 2176/IP 396	°C	190
Four Ball Weld Load	ASTM D2596/DIN51350:4	N	2000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION®**