



CHAMPION ECO FLOW 10W30 SP/RC G6 HC

30/07/2020

16157

This semi-synthetic oil significantly reduces wear and ensures fuel savings and lower CO2 emissions. Optimized additive package reduces soot and deposits and keeps the engine clean.

Application

This product has been specifically developed to meet the challenging requirements of the latest ILSAC GF-6 A standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

Specifications

API	SN Plus SN/RC SP SP/RC
ILSAC	GF-5 GF-6 A

Characteristics

<u>Test</u>	<u>Unit</u>	<u>Method</u>	<u>Average result</u>
Density at 15°C	g/ml	ASTM D4052	0.847
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	64.2
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	10.6
Viscosity index		ASTM D2270	155
B.N. (HCLO4 method)	mg KOH/g	ASTM D2896	8.5
Pour point	°C	ASTM D6892	-42
Flash Point COC	°C	ASTM D92	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION