

## **CHAMPION OEM SPECIFIC 5W30 C3 RN**

16/01/2020

65637

This synthetic engine oil formulation guarantees a cleaner and better performing engine without lowering the oil drain interval. The broad applicability of this lubricant enables you to offer perfect maintenance to different vehicles of several major brands.

## **Application**

This engine oil can be used in systems with or without exhaust gas aftertreatment where C3 engine oils are required. Furthermore, this engine oil has the official Renault RN 17 approval. This means also that you can use this lubricant where RN0700 & RN0710 were previously required, enabling you to service several Dacia and Renault models with this engine oil.

## **Specifications**

ACEA C3

RENAULT RN17 approval

## **Characteristics**

<u>Test</u>	<u>Unit</u>	<u>Method</u>	Average result
Density at 15°C	g/ml	ASTM D4052	0.849
Kinematic viscosity at 40°C	mm²/s	ASTM D4032	60.3
Kinematic viscosity at 100°C	mm²/s	ASTM D445	11.8
Viscosity index		<b>ASTM D2270</b>	197
B.N. (HCLO4 method)	mg KOH/g	<b>ASTM D2896</b>	8.0
Pour point	°C	<b>ASTM D6892</b>	-39
Sulfated Ash	Mass %	ASTM D874	0.78

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.



G. Gilliotstraat 52 – 2620 Hemiksem – Belgium Tel. +32 3 870 00 00 www.championlubes.com

