



## OEM LEVEL 5W30 C3

12/08/2020

75607

### Description

This full synthetic engine oil meets the specifications of different OEMs. Its mid SAPS formulation combines excellent low viscosity properties with highly protective additives, enabling the engine to run more fuel efficient. This product may not be available in your region. Please, consult your local sales contact for more information.

### Application

This engine oil meets the dexos 2 specifications, which means that it can be used to lubricate all new GM/OPEL/Vauxhall and Chevrolet diesel and gasoline passenger cars. Furthermore, it meets different demanding Volkswagen and Mercedes-Benz specifications.

### Specifications

ACEA	C2*	GM dexos 2
	C3	MB 229.31/229.51/229.52
API	SN/CF	VW 502 00/505 00/505 01
BMW	LOGLIFE-04	FIAT 9.55535-S3

### Characteristics

<u>Test</u>	<u>Unit</u>	<u>Method</u>	<u>Average result</u>
Appearance		Visual	B&C
Density at 15°C	g/ml	ASTM D4052	0.854
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	71.4
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	12.1
Viscosity index		ASTM D2270	167
B.N. (HClO4 method)	mg KOH/g	ASTM D2896	7.6
Pour point	°C	ASTM D6892	-45
CCS viscosity at -30°C	mPa.s	ASTM D5293	6082
Flash Point COC	°C	ASTM D92	232

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.