



## OEM LEVEL 5W30 C4

12/08/2020

75614

### Description

This full synthetic engine oil is formulated to meet the specifications of different OEMs. The low SAPS formula guarantees complete DPF protection. Furthermore, its fluidity at low temperatures guarantee easy starting in winter conditions. This product may not be available in your region. Please, consult your local sales contact for more information.

### Application

Can be used for gasoline and diesel engines of passenger cars, more specifically for Renault, requiring the ACEA C4 and RN 720 specifications.

### Specifications

ACEA	C3/C4
FIAT	9.55535-S4
MB	226.51/229.31/229.51
RENAULT	RN 0720

### Characteristics

<u>Test</u>	<u>Unit</u>	<u>Method</u>	<u>Average result</u>
Density at 15°C	g/ml	ASTM D4052	0.851
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	69.1
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	11.7
Viscosity index		ASTM D2270	165
B.N. (HCLO4 method)	mg KOH/g	ASTM D2896	7.2
Pour point	°C	ASTM D6892	-45
Sulfated Ash	Mass %	ASTM D874	0.5
Flash Point COC	°C	ASTM D92	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

**CHAMPION CHEMICALS NV**  
G. Gilliotstraat 52 - 2620 Hemiksem - Belgium  
Tel. +32 3 870 00 00  
[www.championlubes.com](http://www.championlubes.com)

**CHAMPION**