



# **Essential for a worry-free journey.** The ContiTireSealant.

- > Replacement product of original equipment quality "Engineered in Germany"
- > Non-hazardous latex-based tyre sealant
- > Extended shelf life of up to five years
- This squeeze bottle can be used as a replacement for similar products from other manufacturers
- > Sealant bottle can be disposed of in the household waste
- > Usage with any standard compressor for tyre puncture sealing





Continental 3

www.continental-mobility.com

Part number: 17120380000

## **Extended movability in case of a puncture.**

ContiTireSealant restores mobility in case of punctures – quickly and safely. The tyre sealant is transferred with a squeeze bottle into the tyre. The tyre can then be inflated again with any standard compressor for tyre puncture sealing, enabling the onward journey to the nearest garage or tyre service (max. 80 km/h and max. 200 km). ContiTireSealant seals passenger car tyre punctures caused by nails or similar objects with a diameter of up to 6 mm.

#### **Product contents:**

- > 600 ml squeeze bottle
- > User manual
- Plastic gloves
- Nozzle
- > Small bag with valve core remover, valve core and speed warning label

#### **Technical specifications of sealant bottle:**

Sealant amount	Shelf life	Dimensions					
600 ml	5 years	Ø 86 mm × 150 mm					
Weight	Application temperature						
640 g	-30°C to +60°C						

### Application for passenger car tyres:

The product can be used for the tyre dimensions which are shown in the following chart and with a required tyre pressure of up to 300 kPa (3 bar, 43 psi).

														225/	
Tyre width					_								Rim size	235/	
in mm					Tyre	cros	s sec	tion					in inches	245/	
420													<b>D</b> 40	255/	
130						25-	-80						R 10	265/	
195													R 14	275/	
135/	25	30	35	40	45	50	55	60	65	70	75	80		285/	
145/	25	30	35	40	45	50	55	60	65	70	75	80		295/	
155/	25	30	35	40	45	50	55	60	65	70	75	80		305/	
165/	25	30	35	40	45	50	55	60	65	70	75	80		315/	
175/	25	30	35	40	45	50	55	60	65	70	75	80		215/	
185/	_25	30	35	40	45	50	55	60	65	70	75	80	R 15	225/	
195/	25	30	35	40	45	50	55	60	65	70	75	80		235/	
205/	_25	30	35	40	_45_	50	55	60	65	70	75	80		245/	
215/	25	30	35	40	45	50	55	60	65	70	75	80		255/	
225/	_25	30	35	40	45	50	55	60	65	70	75			265/	
235/	25	30	35	40	45	50	55	60	65	70	75			275/	
245/	25	30	35	40	45	50	55	60	65	70				285/	
155/	25	30	35	40	45	50	55	60	65	70	75	80		295/	
165/	_25	30	35	40	45	50	55	60	65	70	75	80		305/	
175/	25	30	35	40	45	50	55	60	65	70	75	80		315/	
185/	25	30	35	40	45	50	55	60	65	70	75	80		225/	
195/	25	30	35	40	45	50	55	60	65	70	75	80	R 16	235/	
205/	25	30	35	40	45	50	55	60	65	70	75			245/	
215/	_25	30	35	40	45	50	55	60	65	70	75			255/	
225/	25	30	35	40	45	50	55	60	65	70	75			265/	
235/	25	30	35	40	45	50	55	60	65	70	75			275/	
245/	25	30	35	40	45	50	55	60	65	70	75			285/	
185/	_25	30	35	40	45	50	55	60	65	70	75	80		295/	
195/	25	30	35	40	45	50	55	60	65	70	75	80		305/	
205/	_25	30	35	40	45	50	55	60	65	70	75			245/	
215/	25	30	35	40	45	50	55	60	65	70	75			255/	
225/	25	30	35	40	45	50	55	60	65	70	75			265/	
235/	25	30	35	40	45	50	55	60	65	70	75		R 17	275/	
245/	25	30	35	40	45	50	55	60	65	70	75			285/	
255/	25	30	35	40	45	50	55	60	65	70	75			295/	
265/	25	30	35	40	45	50	55	60	65	70				305/	
275/	25	30	35	40	45	50	55	60	65					315/	
285/	25	30	35	40	45	50	55	60	65					325/	

Tyre width in mm				Tyr	e cros	s sec	tion				Rim size in inches
205/	25	30	35	40	45	50	55	60	65	70	
215/	25	30	35	40	45	50	55	60	65	70	
225/	25	30	35	40	45	50	55	60	65	70	
235/	25	30	35	40	45	50	55	60	65	70	
245/	25	30	35	40	45	50	55	60	65	70	
255/	25	30	35	40	45	50	55	60	65	70	5.40
265/	25	30	35	40	45	50	55	60	65	70	R 18
275/	25	30	35	40	45	50	55	60	65		
285/	25	30	35	40	45	50	55	60			
295/	25	30	35	40	45	50	55				
305/	25	30	35	40	45						
315/	25	30	35								
215/	25	30	35	40	45	50	55	60	65		
225/	25	30	35	40	45	50	55	60	65		
235/	25	30	35	40	45	50	55	60	65		
245/	25	30	35	40	45	50	55	60	65		
255/	25	30	35	40	45	50	55	60	65		
265/	25	30	35	40	45	50	55	60			R 19
275/	25	30	35	40	45	50	55				
285/	25	30	35	40	45	50					
295/	25	30	35	40	45						
305/	25	30	35	40							
315/	25	30	35								
225/	25	30	35	40	45	50	55	60			
235/	25	30	35	40	45	50	55	60			
245/	25	30	35	40	45	50	55	60			
255/	25	30	35	40	45	50	55	60			
265/	25	30	35	40	45	50	55	60			R 20
275/	25	30	35	40	45	50	55				
285/	25	30	35	40	45	50					
295/	25	30	35	40	45						
305/	25	30	35	40							
245/	25	30	35	40	45	50	55				
255/	25	30	35	40	45	50	55				
265/	25	30	35	40	45	50	55				
275/	25	30	35	40	45	50					
285/	25	30	35	40	45						R 21
295/	25	30	35	40							
305/	25	30	35								
315/	25	30									
325/	25	30									